



evō

techspecs

Model	GWH09AB-A3DNA1B	GWH12AB-A3DNA1B	GWH12AB-D3DNA1B	GWH18AC-D3DNA1B	GWH24AC-D3DNA1B
System Type	Heat Pump				
Power Supply	115V / 60Hz	115V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz
Rated Current (Amps) Cooling	8	13	5	12	12.2
Rated Current (Amps) Heating	8.5	14.5	5.5	12.4	12.5
System Performance					
Cooling Capacity (BTU/h)	9,000	12,000	12,000	18,000	21,000
Heating Capacity (BTU/h)	9,500	11,700	13,000	25,000	26,000
SEER/EER	23 / 14.3	22 / 12.5	22 / 12.5	20 / 12	18 / 12
HSPF	9.8	8.9	10.5	10.2	10.2
Indoor Unit					
Air Flow (CFM)	300	300	330	500	600
Sound Pressure Level - T/H/M/L (dBA)	42/38/30/28	42/38/30/28	47/38/30/28	46/43/40/35	51/43/40/35
Unit Dimensions (W" x H" x D")	34.3 x 11.1 x 7	34.3 x 11.1 x 7	34.3 x 11.1 x 7	37.7 x 11.8 x 7.7	42.9 x 12.9 x 8.2
Package Dimensions (W" x H" x D")	36.8 x 14.7 x 10.2	36.8 x 14.7 x 10.2	36.8 x 14.7 x 10.2	40.7 x 15 x 11	45.6 x 16.1 x 12.2
Net / Gross Weight (lbs)	26 / 33	26 / 33	26 / 33	28 / 39	35 / 46
Outdoor Unit					
Compressor Type	DC Inverter-Driven Twin Rotary				
Sound Pressure Level (dBA)	52	55	55	54	56
Unit Dimensions (W" x H" x D")	33.3 x 21.3 x 12.6	33.3 x 23.2 x 12.6	33.3 x 23.2 x 12.6	35 x 27.5 x 13.4	36.2 x 31.1 x 14.5
Package Dimensions (W" x H" x D")	34.5 x 22.8 x 14.2	34.5 x 24.8 x 14.2	34.5 x 24.8 x 14.2	40.5 x 28.9 x 18.1	41.9 x 33 x 19
Net / Gross Weight (lbs)	88 / 96	90 / 99	90 / 99	110 / 121	118 / 132
Refrigerant / Charge (oz)	R410A / 47.6	R410A / 47.6	R410A / 45.8	R410A / 51.1	R410A / 63.4
Installation					
Line Set Size, Liquid - Suction (in.)	1/4 - 3/8	1/4 - 1/2	1/4 - 1/2	1/4 - 1/2	1/4 - 5/8
Pre-Charge (ft)	16	16	16	25	25
Max. Line Run (ft)	66	66	66	100	100
Max. Elevation (ft)	33	33	33	50	50
MCA (Amps)	12.2	12.2	6.2	14	14
MOCP (Amps)	25	25	10	25	25
Wire Size / # Wires	AWG16 / 4				

Features						
Automatic operation	I Feel automatic comfort option	5-year limited parts warranty	Photocatalytic filter	Comfortable Sleep Mode	Intelligent Defrost	LED controls
Self-diagnosis	Turbo button	Control lock	Wide angle louvers	Air flow direction control	Gold Fin condenser	Multiple fan speeds
Memory function	Wireless remote	Fan Delay function	LED clock display	Timer	Auto Clean	Drying operation



Indoor units available from 9,000-21,000 BTU/h

Outdoor units include a DC inverter-driven twin rotary compressor



Preserving resources remains our top priority, so we've printed this piece on recycled materials.

place mixed sources FSC logo here

greecooling.com



For more information, visit ACdoctor.com

Test conditions are based on AHRI 210/240. Specifications are subject to change without notice. Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations. ©2011. All rights reserved. WAT11940